



## SB41120/B700 - FriFri Basic+ 411 Electric Built- in Single Tank Fryer - 2 Baskets - W 400 mm - 15.0 kW

High-performance frying has never been as easy as it is with the FriFri 15kW Basic+ 411 Built-In Fryer.

- ✓ Superb temperature control for consistently excellent results. Highly responsive digital electronic control able to maintain oil to +/-1 °C of the temperature selected
- ✓ Vertically coiled element for greater surface contact with oil, delivering fast recovery and preventing oil from scorching and degrading
- ✓ Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri<sup>®</sup> integrated oil pump and filtration system, increases efficiency, convenience and safety while extending oil life and saving you money
- ✓ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning

### Specifications

#### Summary

<b>Brand</b>	FriFri
<b>Range</b>	Basic+
<b>Power Type</b>	Electric
<b>Unit Type</b>	Built-in
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour Warranty
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105115373

#### Power and Performance

<b>Total Power kW</b>	15.0
<b>Temperature Range °C</b>	60-190
<b>IP Rating</b>	IP25
<b>Temperature Control</b>	Electronic

#### Key Specifications

<b>Number of Baskets</b>	2
<b>Number of Tanks</b>	1
<b>Gravity Filtration</b>	Yes
<b>Pumped Filtration</b>	No
<b>Drain Location</b>	Through the body

#### Capacity

<b>Product Output per Hour</b>	36kg fries - 7mm [frozen]
<b>Capacity Litres</b>	17.0-20.5

#### Weights and Dimensions

<b>Unit Height (External) mm</b>	537
<b>Unit Width (External) mm</b>	400
<b>Unit Depth (External) mm</b>	630
<b>Net Weight Kg</b>	57

#### Supply Connections

<b>Requires Installation</b>	Yes
<b>Requires Electrical Supply</b>	Yes
<b>UK 3 Pin Plug</b>	No
<b>Requires Hardwiring</b>	Yes
<b>Electrical Supply Rating Watts</b>	15,000
<b>Three Phase Amps</b>	L1=21.7; L2=21.7; L3=21.7
<b>Three Phase Voltage</b>	400
<b>Number of Supply Cables</b>	1

#### Shipping

<b>Packed Weight Kg</b>	62.7
<b>Packed Height cm</b>	72
<b>Packed Width cm</b>	89
<b>Packed Depth cm</b>	80

## Available Options

### Oil Pump

OP1

1 Oil Pump

### Baskets

411\_1\_BASKET

1 Basket

411\_2\_BASKETS

2 Baskets

## Available Accessories

**FZ100831**

SMALL BASKETS FOR 211 411 412 422 - COMPLETE WITH HANDLE

**FZ411048**

LARGE BASKET FOR 411 - 5MM MESH - COMPLETE WITH HANDLE



### Lincat Limited

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



### Customer Care

**Tel:** +44 1522 875500

**Email:** care@lincat.co.uk

### Export Customers

**Tel:** +44 1522 875536

**Email:** export@lincat.co.uk

### Opening Hours

**Monday – Friday:**

8.30am – 5pm